

## DURA CRIB<sup>®</sup> BRAND PRODUCTS WORKING LOAD REFERENCE GUIDE

## PLEASE POST THE FRONT AND BACK OF THIS GUIDE IN A CONSPICUOUS AREA WHERE PRODUCTS ARE BEING USED.

NOTE: Please read the Dura Crib Safety & Reference Manual prior to using these products. Product working load limits are maximized in a 77-degree Fahrenheit (25-degree Celsius) environment; temperatures above or below will decrease working load limits.

PLEASE CONTACT YOUR DISTRIBUTOR WITH ANY QUESTIONS OR CONTACT TURTLE PLASTICS AT: 7400 Industrial Parkway Drive Lorain, OH 44053 1-800-756-6635 or 440-282-8008 info@turtleplastics.com	Product Photo		
www.turtleplastics.com or	Capacity	Heavy Duty	Heavy Duty
https://www.turtleplastics.com/resources/	Mfg. Part #	S612-24	S612-12
or scan the QR Code for the online resource page.	Product Name	The Slab®	Half Slab®
<image/> <image/>	Working Load (KG/LBS)	110,000/242,508	55,000/121,254
	PSI	865	865
	Product Photo		
	Capacity	Heavy Duty	Heavy Duty
	Mfg. Part #	66SC-36	67HDC-30
	Product Name	Super Crib XL® - Platform Base Crib Block	Black Diamond Crib®
	Working Load (KG/LBS)	78,400/172,842	71,600/157,850
	PSI	865	865
	Product Photo		
DO NOT OVERLOAD PRODUCTS.	Capacity	Heavy Duty	Heavy Duty
INSPECT PRODUCTS FOR ANY DAMAGE     PRIOR TO USING.	Mfg. Part #	67PC-24	44HDC-30
DO NOT DRILL INTO OR MODIFY     PRODUCTS.	Product Name	Prime Crib®	Profile Crib®
ALL TURTLE PLASTICS" PRODUCTS	Working Load (KG/LBS)	58,800/129,631	50,800/111,994
	PSI	865	865



Product Photo				
Capacity	Medium Duty	Light Duty	Light Duty	Light Duty
Mfg. Part #	67SC-24	1B, 2B, 3B	67HDC-10	44PL-18
Product Name	Super Crib®	Turtle Lock Block/Blox®	Little Black Diamond Crib®	Hybrid Crib®
Working Load (KG/LBS)	49,900/110,000	31,000/68,343 per block	23,700/52,249	20,500/45,194
PSI	735	865	865	735
Product Photo			SC-1	
Capacity	Light Duty	Light Duty	Light Duty-Fire Industry	Light Duty-Fire Industry
Mfg. Part #	44-18 Pyramid Crib	24-18 Pyramid Crib	SC-1,SC-2,SC-3	SC-COG-1
Product Name	44-18 Pyramid Crib®	24-18 Pyramid Crib®	Standard, Medium and Giant Step Chock	Cog Step Chock
Working Load (KG/LBS)	13,607/30,000	8,164/18,000	4,400/9,700 per chock	1,701/3,750 without cog or 2,722/6,000 with cog
PSI	735	865	865 each size	865
Protection Pad Product Photo	Стр2424-2			
Capacity	Medium Duty	Super Heavy Duty	Super Heavy Duty	Super Heavy Duty
Mfg. Part #	CTP2424-2 and CTP1818-1.5	SP24-2	PCP24	SP24 and SP12
Product Name	ModPad® (US Pat. No. D804,768)	Slab Pad Two	Prime Crib Stack Pad	Slab Pad and Half Slab Pad
Working Load (KG/LBS)	54,431/102,058 and 120,000/225,000			
PSI	369 and 402	3,000	3,000	3,000
Protection Pad Product Photo			All products are made from 100% recycled plastic and can be cleaned using an approved agent from the EPA List N. Please note products and/or part # may have been changed since your original purchase. If you have any questions, please contact your distributor or Turtle Plastics at: 7400 Industrial Parkway Drive	
Capacity	Medium Duty	Light Duty	7400 Industrial Parkway Drive Lorain, OH 44053 1-800-756-6635 or 440-282-8008 www.turtleplastics.com or info@turtleplastics.com. ©2023 Turtle Plastics®, all rights reserved. This Working Load Guide may be copied but not altered without the written consent of Turtle Plastics®.	
Mfg. Part #	PSP24	PSP18		
Product Name	Single Prime/Super Crib Pad	Single Hybrid Crib Pad		
PSI	3,000	3,000		